

ALUMINIUM SLIDING DOOR

Double skinned aluminium alloy sliding door supplied with bulkhead frame. Door fitted with mortice latch and recessed handle both sides. Complete with sliding door track and bottom channel guide. Bulkhead frame with lockbox and pelmet. Lightweight design to keep weight to a minimum. Door and frame designed for composite or steel bulkhead fitment.

1570MM TRACK LENGTH PELMET WITH CLOSED ENDS DVERFRAME SEE DOORS SLIDING DOOR DOUBLE SKIN ALUM.ALLOY 150 COAMING DOOR ESCAPE PANEL WHERE REQUIRED 50+40+3 SUPPORT ANGLE 75 LONG NYLOCK NUT FRONT ELEVATION -ROLLER (44315) DOOR (CLOSED) PLAN AT SILL 1570MM PLAN AT TRACK C.D. 680 X 50+40+3 ANGLE DOOR (OPEN) 6MM STUD 25-5MM PLT FITTED WITH DOORSTOP 1535MM STANDING DECK PLAN AT BOTTOM CHANNEL DOUBLE SKIN ALUMINIUM SLIDING DOOR. MILD STEEL 'L' SECTION BHD FRAME. SECTION 'THRO' X X SLIDING TRACK FOR TOP, CHANNEL GUIDE FOR BOTTOM.

sales@m-m-l.com